

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



2/9

280

```
<Root>
  <RuleSetID>GUID</RuleSetID>
  <RuleSetName>Name</RuleSetName>
  <RuleSetDescription>Description Text</RuleSetDescription>
  <RuleSetVersion>X.XX</RuleSetVersion>
  <RuleSetRevision>Free Entry Text</RuleSetRevision>
  <RuleSetState>Development/Deployed</RuleSetState>
  <RuleSetAsset>Asset Type</RuleSetAsset>
  <CustomRuleCount>N</CustomRuleCount>
  <CustomRule0>
    Custom Rule (Defined by Template Importer/Exporter)</CustomRule0>
  <CustomRule1>
    Custom Rule (Defined by Template Importer/Exporter)</CustomRule1>
    .....
    .....
  <CustomRuleN>
    Custom Rule (Defined by Template Importer/Exporter)</CustomRuleN>
</Root>
```

284

282

FIG. 2




FIG. 3



5/9




FIG. 5

6/9

600

×

Test Session Wizard – User defined Values

Set Operand Values:

Rule Cycle	1	2	3	4	5	6
Execution Time	0:00	0:04	0:08	0:12	0:16	0:20
Rules	Value	Value	Value	Value	Value	Value
<input type="checkbox"/> Turbine Discharge Temp Rule						
Temp1. Temperature	deg C 455.000	460.000	455.000	460.000	470.000	455.000
Temp2. Temperature	deg C 470.000	470.000	470.000	420.000	470.000	470.000
HorizDisp. Direct	mil 2.500	No Data	2.500	2.500	2.500	2.500
<input type="checkbox"/> Turbine Bearing Rule						
Temp1. Temperature	deg C 455.000	455.000	460.000	455.000	455.000	455.000
Temp2. Temperature	deg C 265.000	265.000	265.000	265.000	265.000	265.000
<input type="checkbox"/> Compressor Rule						
Temp1. Temperature	deg C 455.000	455.000	455.000	460.000	455.000	455.000
Temp2. Temperature	deg C 177.000	Bad Conf	265.000	265.000	265.000	265.000
Discharge Pressure. Pressure	psi 1305.000	1305.000	1315.000	1305.000	1305.000	1305.000
HorizDisp. Direct	mil 1.350	No Data	1.350	1.250	1.250	1.350
HorizDist.1X						
Horiz Disp. 1X. Amplitude	mil 1.230	1.100	1.100	2.660	1.100	1.100
Horiz Disp. 1X. Phase	deg 176.000	178.000	175.000	175.000	178.000	175.000

608

602

610

606

604

◀

▶

Finish

Back

Cancel

FIG. 6

7/9

700




FIG. 7

8/9

800

User Rights ? X

Users:

PSAMER\KELLYBR

802

806 Add User...

808 Remove User

Rights:

- ☒ Edit/Delete Machinery Reference Data
- ☒ Archive Data
- ☒ Clear Alarms
- ☒ Acknowledge Alarms/Events
- ☒ Override Lock
- ☒ Data Acquisition Control
- ☒ CMMS Full Access Rights
- ☒ Import/Export Templates
- ☒ Edit/Delete Decision Support Configuration
- ☒ View Decision Support Configuration

810

OK Cancel Help

FIG. 8

9/9

900

902

Properties of Gas Turbine Rule Set

General Security Versions Documentation

Font: Arial Size: 10 Style: Western

- Rule Set specific documentation goes here.
- This documentation will be packaged with Rule Set.
- This will be a rich text edit control.
- This will enable bullet points, bolding, etc
- Individual rules will have a similar notes tab.

904

OK Cancel Help

FIG. 9